





HPC

Remember?



Remember?




Основные характеристики вычислительного кластера

- Пиковая (теоретическая) производительность (Tflops)
- Linpack производительность (Tflops)
- БогоMIPS производительность?
- Пропускная способность Interconnect (Gbps)
- Задержки Interconnect (ns)


Основные характеристики вычислительного кластера

- Пиковая (теоретическая) производительность (Tflops)
- Linpack производительность (Tflops)
- BogoMIPS производительность?
- Пропускная способность Interconnect (Gbps)
- Задержки Interconnect (ns)



сеть


Что такое компьютерная сеть?




Что такое компьютерная сеть?

- Универсальность (любой компьютер)
- Масштабируемость
- Скорость
- Низкая стоимость


Ethernet




Ethernet




Ethernet



Ethernet




Ethernet



Ethernet



Ethernet



Ethernet




Ethernet


единая шина




Ethernet




Ethernet







Ethernet



Ethernet




Ethernet




Ethernet

- Мне ли пришёл данный кадр?
- Кому слать ответ?




Ethernet

- Мне ли пришёл данный кадр?
- Кому слать ответ?




Ethernet

- Мне ли пришёл данный кадр?
- Кому слать ответ?




Ethernet





Ethernet


- Мне ли пришёл данный кадр?
- Кому слать ответ?



Ethernet



Ethernet



Ethernet

Большая сеть




Ethernet



Ethernet

общая шина, коллизии






Ethernet




Ethernet



Ethernet


repeater




Ethernet

- Плохая масштабируемость
- Низкая надёжность
- Коллизии
- Низкая скорость

Ethernet



Ethernet





Ethernet


COAXIAL CABLE





Ethernet




Ethernet




Ethernet




- **Magnetic field**
- **Induced noise current**




Ethernet



Ethernet




Разрыв, но сеть
рабочоспособна




Ethernet




Ethernet



(a)





(b)





(c)









(a) Концентратор (b) Мост (c) Коммутатор









Ethernet











Ethernet











Ethernet


- Не универсально
- Плохо масштабируемо

Ethernet













Маршрутизатор




Маршрутизатор










Маршрутизатор







IP





IP







IP

0 4 8 16 19 31

Version	Header Length	Service Type	Total Length				
Identification			Flags	Fragment Offset			
TTL	Protocol		Header Checksum				
Source IP Addr							
Destination IP Addr							
Options			Padding				




Маршрутизатор




Маршрутизатор

IP


IP-сеть:




IP




OSI



OSI







- Какому приложению?
- Искажение содержимого?
- Изменение порядка пакетов?
- Фрагментация и другое...




- Какому приложению?
- Искажение содержимого?

контрольная сумма

порт

порядковый номер

- Изменение порядка пакетов?
- Фрагментация и другое...



порт

контрольная сумма


- Какому приложению?
- Искажение содержимого?

порядковый номер


И прочее...

- Изменение порядка пакетов?
- Фрагментация и другое...

TCP




TCP



TCP
header

TCP




TCP




TCP State




TCP State




TCP



TCP




TCP




TCP vs UDP

TCP	UDP
Keeps track of lost packets. Makes sure that lost packets are re-sent	Doesn't keep track of lost packets
Adds sequence numbers to packets and reorders any packets that arrive in the wrong order	Doesn't care about packet arrival order
Slower, because of all added additional functionality	Faster, because it lacks any extra features
Requires more computer resources, because the OS needs to keep track of ongoing communication sessions and manage them on a much deeper level	Requires less computer resources
Examples of programs and services that use TCP: <ul style="list-style-type: none">- HTTP- HTTPS- FTP- Many computer games	Examples of programs and services that use UDP: <ul style="list-style-type: none">- DNS- IP telephony- DHCP- Many computer games


User TCP/IP




User TCP/IP



User TCP/IP




User TCP/IP



Infiniband & RDMA


**TCP/IP over
Ethernet:**




Infiniband & RDMA

TCP/IP over
Ethernet:


внутри тоже
буферы




Infiniband & RDMA




Infiniband & RDMA



Infiniband & RDMA



Infiniband & RDMA



Throughput	1 Gbps	3.9 Gbps	4.1 Gbps	4.5 Gbps	7.9 Gbps	8 Gbps	8 Gbs
Latency	40 usec	40 usec	20 usec	15 usec	15 usec	8 usec	4.5 usec
CPU Utilization	30%	80%	85%	25%	4%	1%	>1%


MPI: Message Passing Interface

* данные за 2006-ой год

SRP: SCSI Remote Protocol

uDAPL: User-level Direct Access Programming Language

Infiniband & RDMA



Throughput	1 Gbps	3.9 Gbps	4.1 Gbps	4.5 Gbps	7.9 Gbps	8 Gbps	8 Gbs
Latency	40 usec	40 usec	20 usec	15 usec	15 usec	8 usec	4.5 usec
CPU Utilization	30%	80%	85%	25%	4%	1%	>1%


MPI: Message Passing Interface

SRP: SCSI Remote Protocol

uDAPL: User-level Direct Access Programming Language

FDR: 700ns
EDR: 500ns

Infiniband & RDMA



Throughput	1 Gbps	3.9 Gbps	4.1 Gbps	4.5 Gbps	7.9 Gbps	8 Gbps	8 Gbs
Latency	40 usec	40 usec	20 usec	15 usec	15 usec	8 usec	4.5 usec
CPU Utilization	30%	80%	85%	25%	4%	1%	>1%

MPI: Message Passing Interface


SRP: SCSI Remote Protocol

uDAPL: User-level Direct Access Programming Language

Latencies


Event	Latency	Scaled
1 CPU cycle	0.3 ns	1 s
Level 1 cache access	0.9 ns	3 s
Level 2 cache access	2.8 ns	9 s
Level 3 cache access	12.9 ns	43 s
Main memory access (DRAM, from CPU)	120 ns	6 min
Solid-state disk I/O (flash memory)	50–150 µs	2–6 days
Rotational disk I/O	1–10 ms	1–12 months
Internet: San Francisco to New York	40 ms	4 years
Internet: San Francisco to United Kingdom	81 ms	8 years
Internet: San Francisco to Australia	183 ms	19 years
TCP packet retransmit	1–3 s	105–317 years
OS virtualization system reboot	4 s	423 years
SCSI command time-out	30 s	3 millennia
Hardware (HW) virtualization system reboot	40 s	4 millennia
Physical system reboot	5 m	32 millennia

File systems in HPC




File systems in HPC

Network file system:




File systems in HPC

Clustered file system:




File systems in HPC

Distributed file system:



File systems in HPC



File systems in HPC


Parallel file system:

- Параллельный доступ ко всем серверам
- Параллельный доступ к данным
- Распределение нагрузки

Fully parallel file system:

- + Параллельный доступ к метаданным

File systems in HPC



Q&A